



999.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Comet Lake !
- Barebone !
- i5-10210U CPU !
- NEW VERSION !

12/22: New Version with Intel® I225-V 2.5GbE LAN

- Intel® Comet Lake i5-10210U 1.6G QC Processor
- 2* DDR4 2666MHz up to 64GB
- 1* Intel® I219LM GbE, 1* Intel® I225-V 2.5GbE
- 1* M.2 (M-key, SATA interface), 1* M.2 (E-key, support CNVi)
- 1* RS232/RS422/485, 4* USB3.2
- Support 1* DP, 2* HDMI
- 12~24V DC-in

Model	- HBJC330U95V-10210 (CPU : 10210U, default) - HBJC330U95VI-10210 (CPU : 10210U, Wifi) - HBJC330U95V-5205 (CPU : 5205U) - HBJC330U95VI-5205 (CPU : 5205U, Wifi)
-------	---

CPU/Chipset	– Intel® Comet Lake i5-10210U 1.6G QC SoC Processor – Intel® Comet Lake 5205U SoC Porcessor
BIOS	– AMI 128MB SMT Flash ROM
Memory	– 2 * DDR4 2666MHz SO-DIMM up to 64GB
Network	– 1* Intel® I219LM GbE – 1* Intel® I225-V 2.5GbE
Graphics	– 1* HDMI1.4 (Max Resolution : 4096×2304@30Hz) – 1* HDMI2.0 (Max Resolution : 4096×2304@60Hz) – 1* DP (Max Resolution : 4096×2304@60Hz) – Support Triple Displays
Storage	– 1 * M.2 (M-Key, 2242, SATA interface)
Expansion	– N/A
Rear Panel I/O	– 2 * USB3.2 (Gen2) – 1 * DP1.4 – 1 * HDMI2.0 – 1 * HDMI1.4 – 2 * RJ45 – 1 * DC Jack (12~24V)
Front Panel I/O	– 1 * Audio Jack (Line out +MIC) – 2 * USB3.2 (Gen2) – 1 * RS232/422/485 – 1 * Power Button
Internal Connector	– 1 * M.2 (M-Key, SATA Interface) – 1 * M.2 (E-Key) for CNVi or PCI-E/USB WIFI/BT – 8bit GPIO – 2 * USB2.0
Power Source	– 12~24V DC-in – Adapter: DC 19V/6.32A 120W
Compliance	– CE, FCC, RoHS, ErP Ready (Option)
Temperature	– Operating Temperature: -10 ~ 50° C – Storage Temperature: -20 ~ 60° C
Dimensions	– 150 (W) x 106 (D) x 75 (H) mm
OS Support	– Windows 10, Linux