

# Android Rugged Tablet

Improve Productivity  
for Mobile Workers  
Even in Extreme  
Conditions



**OS**  
Android 14



**Performanc**  
Octa-Core Processor



**Wireless**  
WiFi, Bluetooth



**Battery**  
Long-lasting 6300mAh



**Operating Temp.**  
-20°C to 60°C



**Camera**  
20MP Autofocus  
with flash



**Display**  
8" IPS  
( 1280x800 )



**Drop Resistance**  
Multiple 1.2 m (4 ft)  
drops per MIL STD 810G

## Cradle Design

RJ45, RS232 interface and OTG supported

## Extended Features

Barcode reader

Camera hub support up to 4 1080p camera input and  
with HDD loop recording capacity

## NFC

Front access, easy for driver to login

## Network

2G / 3G / 4G with voice; Proved reliability network  
connection

## MDM Remote Control Server

Topicon's device management server is developed to allow  
customer to update different firmware and make kiosk mode

## Specification

PERFORMANCE CHARACTERISTICS	
CPU	2.0GHz Octa Core Processor
OS	Android 14 GMS or NON GMS
Memory	4GB LPDDR4X 64GB eMMC
PHYSICAL CHARACTERISTICS	
Dimensions	227mm L x 156mm W x 22 mm D
Weight	825g
Display	8inch, IPS panel (1280 x 800 pixel)
Touch Panel	Capacitive multi-touch / Glove, Wet, Stylus
Backlight	LED Backlight
Power	Rechargeable Lithium-ion Battery 3.7V 6300mAh
Expansion Slot	User accessible micro SD cardslot (standard supports up to 512GB)
SIM	1x Standard-SIM
Interface	1xUSB Type C 2.0 OTG  1x3.5mm Audio Headphone Jack  1x Mini USB 2.0 OTG on the cradle
Notification	Audible tone, Charging Status LED
Voice / Audio	Speaker, Microphone, headphone
Keypad	On-screen keypad
WIRELESS WAN DATA AND VOICE COMMUNICATION	
Radio Frequency	2G-GSM: 850,900, 1800, 900MHz 3G-WCDMA: B1, B2, B4, B5, B8 4G-LTE FDD: B1, B2, B3, B4, B5, B7, B8, B12, B17, B20, B28, B66 4G-LTE TDD: B40, B38, B41
GNSS	GPS, GLONASS, GALILEO
WIRELESS LAN	
Radio	802.11 a/b/g/n/ac; 802.11 d/e/h/i/j/k/r/v/w
Data Rate	5GHz: 802.11a/n/ac — up to 500 Mbps; 2.4GHz: 802.11b/g/n — up to 144Mbps
Security and Encryption	WFA WPA/WPA2 Personal, AES-CCMP, WPI-SMS4, GCMP, WPS2.0, WAPI (hardware)

WIRELESS PAN	
Bluetooth	V5.0
WIRED LAN	
Ethernet (Optional)	Support (w/Cradle)
DATA CAPTURE	
Scanner (Optional)	1D&2D Imagers
Camera	Rear camera 20MP
Video Input (Optional)	Support one channel AHD 720P,1080P analog camera (w/Cradle) Support four channels AHD 720P,1080P analog camera (w/Camera Hub)
NFC	Supported TAG-ICs: MIFARE Classic 1k/4k/Plus, MIFARE UltraLight MIFARE UltraLight C, MIFARE DESFire MIFARE DESFire Ev1, ISO 14443 A & B ISO 15693
Serial Communication	1 x RS232
SENSOR	
Light Sensor	Ambient Light
Motion Sensor	Accelerometer, E-Compass, Gyroscope
USER ENVIRONMENT	
Operating Temp.	-20°C to 60°C / -4°F to 140°F
Storage Temp.	-20°C to 70°C / -4°F to 158°F
Humidity	90% non-condensing
Drop Spec.	1.2m / 4 ft. to drop per MIL STD 810G
Sealing	IP67
Electrostatic Discharge (ESD)	+/-8kVdc air discharge +/-4kVdc direct discharge +/-4kVdc indirect discharge
OPTIONAL ACCESSORIES	
Vehicle docking station Metal dash mount NFC reader at docking station Extra input and output at docking station	
* Specification is subject to change.	